

#86774 MicroLux Roto Buffer Instructions

To open the battery compartment, use a coin in the notch towards the back end of the tool to pry up and remove the lid.



Install 2 AA batteries according to the diagram molded in the battery compartment.

Push the button to power on, release to power off.

To replace or adjust the length of the abrasive tip, pull tip and metal clamping collet out of the end of the tool, then push back in to reinstall. Abrasive tip will need replacing when it wears down to about 1/4" in length...see #86774A at www.micromark.com.

Micro-Mark® 340 Snyder Avenue
Berkeley Heights, NJ 07922
Tech Support: MMTechService@micromark.com
www.micromark.com MM090716

#86774 MicroLux Roto Buffer Instructions

To open the battery compartment, use a coin in the notch towards the back end of the tool to pry up and remove the lid.



Install 2 AA batteries according to the diagram molded in the battery compartment.

Push the button to power on, release to power off.

To replace or adjust the length of the abrasive tip, pull tip and metal clamping collet out of the end of the tool, then push back in to reinstall. Abrasive tip will need replacing when it wears down to about 1/4" in length...see #86774A at www.micromark.com.

Micro-Mark® 340 Snyder Avenue
Berkeley Heights, NJ 07922
Tech Support: MMTechService@micromark.com
www.micromark.com MM090716

#86774 MicroLux Roto Buffer Instructions

To open the battery compartment, use a coin in the notch towards the back end of the tool to pry up and remove the lid.



Install 2 AA batteries according to the diagram molded in the battery compartment.

Push the button to power on, release to power off.

To replace or adjust the length of the abrasive tip, pull tip and metal clamping collet out of the end of the tool, then push back in to reinstall. Abrasive tip will need replacing when it wears down to about 1/4" in length...see #86774A at www.micromark.com.

Micro-Mark® 340 Snyder Avenue
Berkeley Heights, NJ 07922
Tech Support: MMTechService@micromark.com
www.micromark.com MM090716

#86774 MicroLux Roto Buffer Instructions

To open the battery compartment, use a coin in the notch towards the back end of the tool to pry up and remove the lid.



Install 2 AA batteries according to the diagram molded in the battery compartment.

Push the button to power on, release to power off.

To replace or adjust the length of the abrasive tip, pull tip and metal clamping collet out of the end of the tool, then push back in to reinstall. Abrasive tip will need replacing when it wears down to about 1/4" in length...see #86774A at www.micromark.com.

Micro-Mark® 340 Snyder Avenue
Berkeley Heights, NJ 07922
Tech Support: MMTechService@micromark.com
www.micromark.com MM090716

#86774 MicroLux Roto Buffer Instructions

To open the battery compartment, use a coin in the notch towards the back end of the tool to pry up and remove the lid.



Install 2 AA batteries according to the diagram molded in the battery compartment.

Push the button to power on, release to power off.

To replace or adjust the length of the abrasive tip, pull tip and metal clamping collet out of the end of the tool, then push back in to reinstall. Abrasive tip will need replacing when it wears down to about 1/4" in length...see #86774A at www.micromark.com.

Micro-Mark® 340 Snyder Avenue
Berkeley Heights, NJ 07922
Tech Support: MMTechService@micromark.com
www.micromark.com MM090716

#86774 MicroLux Roto Buffer Instructions

To open the battery compartment, use a coin in the notch towards the back end of the tool to pry up and remove the lid.



Install 2 AA batteries according to the diagram molded in the battery compartment.

Push the button to power on, release to power off.

To replace or adjust the length of the abrasive tip, pull tip and metal clamping collet out of the end of the tool, then push back in to reinstall. Abrasive tip will need replacing when it wears down to about 1/4" in length...see #86774A at www.micromark.com.

Micro-Mark® 340 Snyder Avenue
Berkeley Heights, NJ 07922
Tech Support: MMTechService@micromark.com
www.micromark.com MM090716